



## TEST CERTIFICATE

### WS 1821 S CRACK 2

Certificate nº: 20240358

Date: 19/4/24

Batch Nr.: 20240358 EXP: 4/27

Manufactured on: 19/4/24

Use Before: 4/27

Penetrant inspection materials are tested in accordance with following specifications (last revision):

- AMS 2644 - ASTM E-165 A4
- ISO 3452-2
- ASME Section V, Article 6, T641 - ASME Section III- NC
- Content of sulphur and halogens method according RCC-M F6000 Annex FV

TEST	METHOD	SPECIFICATION	RESULT
Removability	AMS 2644E 3.3.10.4	According to standard	According to standard
Fluorescence	AMS 2644E 3.3.10.2	According to standard	According to standard
Performance	EN-ISO 3452-2 6.15	According to standard	According to standard
Cl + F	ASTM E 165-02 (A4) EPA 300.0	< 350 ppm	< 200 ppm
S	ASTM E 165-02 (A4) EPA 300.0	< 200 ppm	< 200 ppm
Cl	ASTM E 165-02 (A4) EPA 300.0	< 1000 ppm	< 200 ppm
F	ASTM E 165-02 (A4) EPA 300.0	< 50 ppm	< 50 ppm
Na	EPA 300.7	< 50 ppm	< 50 ppm

According to the above mentioned specification the material is acceptable.

Joan Colom Ingeniero Químico, I.Q.S.

WHALE SPRAY, S.L.

