



HT56

Specifications	HT56	HT56C
Combustible Gas Detection	100~5000ppm	100~5000ppm
Accuracy	±30%	±30%
Display	LCD	LCD
Auto Power Off	✓	✓
Low Battery Indication	✓	✓
Two-Colour Backlight	✓	✓
Buzzer Alert	✓	✓
Power	2x1.5V AAA batteries	3.7V Lithium batteries
Weight	Approx.35g	Approx.35g
Size	170X23X28mm	170X23X28mm
QTY	200pcs	200pcs
Safety Rating	EN61326-1	EN61326-1



HT56Pro

Specifications	
Combustible Gas Detection	100~5000ppm
Accuracy	≤10% FS(methane)
Sensitivity	< 100ppm(methane)
Response Time	≤500ppm Approx.5sec >500ppm Approx.2sec
Warm-Up Time	Approx. 30 sec
Display	LCD
Alarm Mode	Visible, audible
Auto Zero	✓
Auto Power Off	✓
Low Battery Indication	✓
Power	2 x1.5V AAA batteries
Weight	Approx. 46g
Size	180X32X31mm
QTY	80pcs
Safety Rating	EN61326-1



HT58Pro

Specifications	Range	Resolution	Basic accuracy
Combustible gas detection	1~20%LEL (100~10000ppm)	1%LEL	±30%
Display	LCD		
Alarm mode	And backlight alarm		
Signal intensity display	Level 20 analog bar+ value percentage		
Signal intensity indication method	sound from slow to fast: The screen changes from green to red		
Auto Power Off	No operation, no sensing signal will shut down automatically in about 5 minutes.		
Flash Light	✓		
Low battery indication	✓		
Trichromatic backlight	✓		
Buzzer alert	✓		
Charging function	✓		
Power	3.7V Lithium batteries		
Weight	Approx.131.5g		
Size	121x56x27mm		
QTY	50pcs		
Safety Rating	EN61326-1		



Specifications	Range	resolution	Basic accuracy
Combustible Gas Detection	0~20%LEL(0~9999ppm)	1%LEL	±1%
Display	LCD		
Alarm mode	Sound and light alarm		
Signal intensity display	Level 20 analog bar+ value percentage		
Signal intensity indication method	sound from slow to fast:		
Auto Power Off	No operation, no sensing signal will shut down automatically in about 5 minutes.		
FLASH LIGHT	✓		
Low battery indication	✓		
Buzzer alert	✓		
Charging function	✓		
Power	3.7V Lithium batteries		



HT608



Natural Gas

LPG

Gasoline

Butane

Gas Fuel

Propane

Ethanol

Alcohol