



Specifications	Range	Accuracy
Lux/FC	0~200000 LUX/0~20000 FC	±(3.0% +5)
Temperature	-20°C~60°C(-4°F~140°F)	0.0°C ~ 45.0°C(32°F ~113°F) : ±1.0°C/2.0°F Other: ±1.5°C/3.0°F
Humidity	0.0%~99.9%RH	20%~ 80%: ±5.0RH other: ±6.0RH
Data Hold	✓	
Backlight	✓	
Max/Min Hold	✓	
Auto Power Off	✓	
Low Battery Indication	✓	
Power	3x1.5V AAA batteries	
Weight	Approx.136g	
Size	142X58X28mm	
QTY	50pcs	
Safety Rating	EN61326-1	



Specifications	HT620	HT620L
Range	1000/10000/200000 LUX; 100/1000/20000 FC	
Accuracy	±(3.0%+5)	±(3.0%+5)
Customization of light source coefficient		Standard light -L0
		White LED light -L1
		Red LED light -L2
		Yellow LED light -L3
		Green LED light -L4
		Blue LED light -L5
		Purple LED light -L6
		Self-defined light source coefficient -L7
		Self-defined light source coefficient -L8
	Self-defined light source coefficient -L9	
Display	LCD bargraph	
Auto/Manual Range	✓	
Data Hold	✓	
Max/Min/Avg Hold	✓	
Relative Value	✓	
Auto Power Off	✓	
Low Battery Indication	✓	
Power	3x1.5V AAA batteries	
Weight	Approx.142g	
Size	190X60X33mm	
QTY	40pcs	
Safety Rating	EN61326-1	

