



Specifications	HT622A	HT622B
Sound Pressure Accuracy	±1.5dB (94dB @ 1KHz) 、 ±5dB (94dB@8KHz)	±1.5dB (94dB @ 1KHz) 、 ±5dB (94dB@8KHz)
Frequency Response	30Hz — 8KHz	30Hz — 8KHz
Dynamic Range	50 dB	50 dB
Measuring Range	30—130dBA	30—130dBA 、 30—130dBC
Weighting Properties	A	A /C
Time Properties	FAST 125ms, SLOW 1sec	FAST 125ms, SLOW 1sec
Microphone	Polarized capacitance microphone	Polarized capacitance microphone
Range	30—80dB、 40—90dB、 50—100dB、 60—110dB、 70—120dB、 80—130dB	30—80dB、 40—90dB、 50—100dB、 60—110dB、 70—120dB、 80—130dB
Bargraph	✓	✓
Auto/Manual Range	✓	✓
Under/Over Range	UNDER/OVER	UNDER/OVER
Backlight	✓	✓
Data Hold	✓	✓
Max/Min Hold	✓	✓
Auto Power Off	✓	✓
Low Battery Indication	✓	✓
USB		✓
Power	3x1.5V AAA batteries	
Weight	Approx. 176g	
Size	189X60X33mm	
QTY	40pcs	
Safety Rating	EN61326-1	

