

NEW



Function		
Non-contact RPM (99999RPM)	$\pm(0.05\%+1)$	
Count (99999R)	✓	
Maximum Count	99999count	
Auto/Manual Range	Auto	
Display	VA	
Effective measurement distance	1000mm	
Analog Bar	✓	
Maximum/Minimum/Average Value Measurement	✓	
Data Hold	✓	
Low Battery Indicator	✓	
Automatic Power-off	✓	
Backlight	✓	
Power Supply	1x6F22 battery	



HT670/HT671 Digital Tachometer

Function	Range	Accuracy	
		HT670	HT671
Non-contact RPM	99999RPM	$\pm(0.05\%+1)$	$\pm(0.05\%+1)$
Contact RPM	20000 RPM	✗	$\pm(0.05\%+1)$
Contact Linear Speed (inch/min)	99999inch/min	✗	$\pm(0.05\%+1)$
Contact Linear Speed (ft/min)	6560 ft/min	✗	$\pm(0.05\%+1)$
Contact Linear Speed (m/min)	0~1999.9m/min	✗	$\pm(0.05\%+1)$
Count	99999R	✓	✗
Maximum Count	99999 Count	99999 Count	99999 Count
Auto/Manual Range	Auto	Auto	Auto
Display	LCD	LCD	LCD
Analog Bar	✓	✗	✗
High/Low Threshold Setting	✓	✓	✓
Threshold Alarm	✓(Audio Alarm and Visual Alarm)	✓(Audio Alarm)	✓(Audio Alarm)
Maximum/Minimum/Average Value Measurement	✓	✓	✓
Data Hold	✓	✓	✓
Low Battery indicator	✓	✓	✓
Automatic Power-off	✓	✓	✓
PC Software	✗	✓	✓
Dual-Coor Backlight	✓	✗	✗
Power Supply	3x1.5 V AAA batteries	700mAh lithium battery	700mAh lithium battery
Accessories	✗	Contact Line Speed Accessory *1 Contact RPM Accessory, Cylindrical *1 Contact RPM Accessory, Large Conical *1 Contact RPM Accessory, Small Conical *1	
Weight	Approx.140g	Approx.140g	Approx.140g
Dimensions	142x58x27.5mm	184x60x33mm	184x60x33mm
QTY	50Pcs		
Safety Rating	EN61326-1		

